

UV LOW ODOUR GLOSS VARNISH

DESCRIPTION	High gloss varnish designed for odour sensitive applications.
PROPERTIES	High gloss Good chemical and product resistance Good adhesion Low residual odour Not suitable for foil blocking/thermal transfer
APPLICATION	Stir well before use Anilox 120 – 160 l/cm Film weight 4-6 g/cm ³ Rollers EPDM UV lamps minimum 80 w/cm
SUBSTRATES	Coated paper and board Top coated thermal paper Treated/primed polyethylene Treated/primed polypropylene Aluminium foils Polyester PVC
STORAGE & HANDLING	Store at temperatures between 5°C and 25°C. Protect from sunlight. In unopened containers EL203 has a shelf life of 12 months.
PACKAGING	10kgs, 25kgs, 1000kgs
AUXILIARY PRODUCTS	RLA 301 Flow agent RLA 302 Photoinitiator RLA 309 UV thinner RLA 350 UV wash up

DISCLAIMER

The information contained in this data sheet is correct to the best of our knowledge. It is intended as a guide only for the optimum use of the named product(s) and is not intended as a warranty or as a specification. This datasheet may not be suitable for combinations with other materials or in processes other than those specifically described. The user should always make their own tests to establish that the product(s) meets their requirements.