

UV HIGH RESISTANCE GLOSS VARNISH

DESCRIPTION	Gloss varnish for general purpose use including labels and packaging. Offering fast cure speed and excellent resistance properties.
PROPERTIES	High gloss Fast cure Low viscosity Very good chemical and product resistance Good adhesion Not suitable for foil blocking/thermal transfer
APPLICATION	Stir well before use Anilox 120 – 160 l/cm Film weight 4-6 g/cm ³ Rollers EPDM UV lamps minimum 80 w/cm
SUBSTRATES	Coated paper and board Top coated thermal paper Treated/primed polyethylene Treated/primed polypropylene Aluminium foils Polyester, PVC
STORAGE & HANDLING	Store at temperatures between 50C and 250C. Protect from sunlight. In unopened containers EL232 has a shelf life of 12 months.
PACKAGING	5kgs, 1000kgs
AUXILIARY PRODUCTS	RLA 301 Flow agent RLA 302 Photoinitiator RLA 309 UV thinner RLA 350 UV wash up

DISCLAIMER

The information contained in this data sheet is correct to the best of our knowledge. It is intended as a guide only for the optimum use of the named product(s) and is not intended as a warranty or as a specification. This datasheet may not be suitable for combinations with other materials or in processes other than those specifically described. The user should always make their own tests to establish that the product(s) meets their requirements.